

WATER CUT-OFF MASTIC

ClassicBond Water Cut-Off Mastic is a one-component, low viscosity, self-wetting, butyl-blend mastic designed to be used in conjunction with ClassicBond roofing systems. It is primarily used as a sealing agent between various membranes and is applicable when a membrane is being terminated using a compression-type seal.

Water Cut-Off Mastic is an extremely tacky material and will remain as such when used with compression-type terminations.

FEATURES & BENEFITS

- Extremely tacky
- Provides a durable compression-type seal between various membranes and parapet wall constructions
- Terminates membranes to compression drainage

COVERAGE RATE

3 linear metres per tube at the recommended application rate of at 13mm bead.

APPLICATION*

1. All surfaces to be sealed with Water Cut-Off Mastic must be free of moisture, oil, dirt and other foreign materials. Fleece backing must be removed from ClassicBond PRO membranes with an electric heat gun. Water Cut-Off Mastic cannot be used on insulation.
2. Apply a 13 mm bead of Water Cut-Off Mastic between the substrate and the edge of the membrane.
3. Apply appropriate termination material and secure to provide constant compression for the Water Cut-Off Mastic.

[Review current specifications and details for specific application requirements.](#)

WATER CUT-OFF MASTIC

PRECAUTIONS

1. Review the applicable Safety Data Sheet for complete safety information prior to use.
2. Water Cut-Off Mastic is **FLAMMABLE** – It contains solvents that are dangerous fire and explosion hazards when exposed to heat, flame or sparks. Store and use away from all sources of heat, flame or sparks. Do not smoke while applying. Do not use in a confined or unventilated area. Vapours are heavier than air and may travel along ground to a distant ignition source and flash back.
3. Avoid breathing vapours. Keep container closed when not in use. Use with adequate ventilation. If inhaled, remove to fresh air. If not breathing, perform artificial respiration. If breathing is difficult, give oxygen. Seek medical attention.
4. If swallowed, **DO NOT INDUCE VOMITING**. Seek medical attention.
5. Avoid contact with eyes. Safety glasses or goggles are recommended. If splashed in eyes, immediately flush eyes with plenty of clean water for at least 15 minutes. Seek medical attention.
6. Avoid contact with skin. Wash hands thoroughly after handling. In case of contact with skin, thoroughly wash affected area with soap and water. Note: Permeation-resistant gloves (that meet ANSI/ISEA 105-2005) are recommended to be worn when using this product to protect hands from irritating ingredients.

Before using this product please ensure that you have been supplied with and have read carefully the following information:

1. The product labels
2. ClassicBond Water Cut-Off Mastic Safety Data Sheet

PROPERTIES AND CHARACTERISTICS

- Solids: 80%
- Colour: Grey
- Flash Point: 4°C
- Service Temperature: -40°C - 93°C
- Specific Gravity: 1.29
- Cold Weather Flex: Excellent
- Viscosity: 1,320,000 Cps
- VOC: 250g/ltr
- Clean Up: Weathered Membrane Cleaner
- Shelf Life: 12 months (unopened container)
- Coverage: 3 linear metre per tube

* Typical properties and characteristics are based on samples tested and are not guaranteed for all samples of this product. This data and information is intended as a guide and does not reflect the specification or specification range for any particular property of this product.