
NBS Specification: ROCKWOOL HARDROCK® Multi-Fix Recovery Board

PRODUCT SUMMARY:

Non-combustible insulation board for refurbishment projects..

PRODUCT GENERAL DESCRIPTION:

Designed to be installed directly on an existing roof, this non-combustible insulation board provides a level surface suitable for receiving a new waterproofing system. The product is faced with a mineral fibre glass tissue facing, which ensures a secure bond between the insulation and an adhered membrane.

FEATURES AND BENEFITS:

- Can be installed directly over the in-situ roof membrane.
- Will accommodate minor imperfections on the existing external finish.
- Can be adhesively applied or mechanically fixed.
- Non-combustible board, ideal for torch applied bitumen systems.
- A single solution that is compatible with most roof coverings.
- Reduces external noise ingress.
- CE marked.

ACOUSTIC PERFORMANCE:

When tested in accordance with BS EN ISO 10140-2:2010 as an individual 30 mm layer within a single ply flat roof system, onto a 0.7 mm profiled steel deck, the system achieved R_w 33 dB.

APPLICATION:

Insulation board for refurbishment projects.

PRODUCT SPECIFICATION CLAUSE

PRODUCT REFERENCE:

ROCKWOOL HARDROCK® Multi-Fix Recovery Board

PRODUCT PROPERTIES:

Standard: BS EN 13162, ISO 14001

Thickness: 30 mm

Thermal conductivity: 0.039 W/mK.

Fire performance: A1 to BS EN 13501-1

Water vapour resistance: 5.9 MNs/gm

CONTACT DETAILS:

ROCKWOOL

Wern Tarw Road, Rhiwceiliog Pencoed, Bridgend CF35 6NY

Email: technical.solutions@rockwool.com

Telephone: 01656 868 490

rockwool.com/uk