

# COLORFAST CF15/19 JT3-2-5.6 x L range

A2 stainless steel bi-met fastener for fixing profiled roofing and cladding sheets to timber sections.

## Application Features

- For fixing profiled roofing and cladding sheets to timber sections
- Available head options CF15 and CF19 aluminium/EPDM vulcanised sealing washers



## Material Specification

- High quality stainless steel grade A2 to ISO 3506, EN 1.4301 to ISO 10088, AISI 304
- Hardened carbon steel drill point and lead threads
- High impact resistant coloured nylon head. Resistant to temperatures from -40°C to 120°C. Colorfast nylon heads are combined with UV stabilisers to ensure maximum colour retention



## Performance Details

### Ultimate Fastener Tensile Strength

Fastener Diameter	kN
5.6 x L	11.10

### Ultimate Fastener Shear Strength

Fastener Diameter	kN
5.6 x L	7.20

### Ultimate Pullout Load kN





Fastener Diameter	Timber Embedment (mm)	
	25	30
5.6 x L	2.15	3.15

Figures based on tests from construction grade timber.

### Ultimate Pullover Load kN

Washer Face	Nominal Sheet Thickness (mm)		
	0.50	0.70	0.90
CF15 Head	5.10	5.75	6.00
CF19 Head	5.50	6.20	6.50

Figures based on use with R38 profile steel sheets with fastener located in valley of profile.



Drive Tool



Self-drilling fastener range

Figures shown on this data sheet are based on results obtained from tests carried out in EJOT UK's Applitec laboratory in accordance with equipment conforming to current industry standards, on a random sample of fasteners manufactured to EJOT tolerances. Information supplied should form part of a general guide and should performance data for a specific application be required please do not hesitate to contact us.