

### PRODUCT SPECIFICATION *HERTALAN*® RAINWATER OUTLETS

#### **HERTALAN®**

Carlisle Construction Materials BV produces and sells a range of synthetic high-quality foils that have been available in the market since 1965. The successful *HERTALAN*® EPDM foil is the best known of those products.

#### **HERTALAN® RAINWATER OUTLETS (HWAs)**

*HERTALAN*® rainwater outlets are designed for *HERTALAN*® roofing systems and offer the security of optimum compatibility with the other *HERTALAN*® products.

<b>HWAs round, PE pipe, length 600 mm</b>									
Drain diameter (mm)	40	50	63	<b>75*</b>	<b>90*</b>	<b>110</b>	<b>125</b>	<b>140</b>	<b>160</b>
Dimensions easy cover flashing	Ø 300 mm					Ø 400 mm			
Dimensions easy weld flashing (l x w in mm)	200	300						400	
Quantity per packaging	60	50	35	30	18	15	10		
Rainwater drain (l/s) in accordance with EN 1253 (incl. leaf catcher)				4.7	4.5	6.0	9.5		10.5

\* From diameter 75 and 90 mm, a 45° drain is also available.

**The diameters 75, 90, 110, 125 and 160 mm have EN 1253 approval.**

<b>HWAs square, PE pipe, length 600 mm</b>		
Drain dimensions (mm)	60 x 80**	60 x 100**
Dimensions easy cover flashing	300 x 300 mm	300 x 300 mm
Dimensions easy weld flashing	300 x 300 mm	300 x 300 mm
Quantity per packaging	20	20

\*\* A 45° and a 90° version are available for both types.

#### **HERTALAN® LEAF CATCHER**

The *HERTALAN*® leaf catcher is required in combination with the diameters (HWA round) 75, 90, 110, 125 and 160 mm if approval in accordance with EN 1253 is required. Test report available on request.

#### **HWAs ROUND AND RECTANGULAR**

The HWAs are fixed in function of the chosen roofing system. For *HERTALAN*® *EASY COVER* it is glued with *KS137* and *KS96*. For the *HERTALAN*® *EASY WELD* system the obvious choice is flashing with prefab *EASY WELD* strips to ensure they can be welded to the substrate by means of hot air.



## Universal *HERTALAN*® LEAF CATCHER

The universal leaf catcher is used when approval in accordance with EN 1253 is required. The universal leaf catcher fits HWAs with a diameter of 75 to 160 mm.



## SITE SLEEVES

For diameters 75, 90, 110, 125 and 160 mm cuffs and site sleeves are also supplied.



Carlisle Construction Materials Ltd.

Ground Floor Office Suite • Lancaster House • Concorde Way • Millennium Business Park • Mansfield Notts NG19 7DW  
T +44 (0)1623 627 285 • F +44 (0)1623 652 741 • info.uk@ccm-europe.com • www.hertalan.co.uk