

## Ecotred 1000 Walkway Tile

Recycled natural black SBR granulate tyre materials in the Ecotred 1000 Walkway Tile provide a variety of colours which can be mixed and matched in eye-pleasing combinations.



Fully Recycled  
& Recyclable



Integrated  
Drainage



B2  
Fire Rated



2 Year  
Guarantee

Drainage channels on the bottom side ensure the free flow of water. The slabs are easily installed over any paved level subsurface and come with an inclusive pegging system.

Material	Polyurethane-bonded recycled tyre granulate
Surface Composition	Smooth with open pores
Under Side Composition	Dimpled underside allowing free drainage
Side Composition	Pre-drilled plastic connector pins included
Colours Available	Black
Dimensional Information	1000mm x 1000mm x 30mm
Area Weight Information	Approx 24 kg/m <sup>2</sup> 45 units to a pallet = 45m <sup>2</sup>
Tensile Strength	147 N/cm <sup>2</sup>
Compression Resistance	16.7 N/cm <sup>2</sup> (before elastic deformation) 200 N/cm <sup>2</sup> (before elastic deformation)
Hardness Shore A	28÷34
Porosity	N / A
Fire Rating	B2 (DIN 4102 Part 1) - Equivalent to Euro Class E
Cold Fracture Resistance	Thermal cycle -30°C for 48h. No defects
Water Flow Capacity	Hydraulic gradient $i = 0,015/0,037 \text{ l}/(\text{m.s})$ lengthwise/ $0,022 \text{ l}/(\text{m.s})$ crosswise

For more information please contact us.